



# Kestopur Voiteluöljy



## AREA OF APPLICATION

Lubricating oil for machinery using one- and two-component adhesive. Used for pistons and needle valves in machines using polyurethane adhesives. Can be used also for the storing of glue nozzles. Refractive index 1.496 - 1.502.

## INSTRUCTIONS FOR USE

Follow machine manufacturer's instructions.

## ADDITIONAL INFORMATION

The information given in this product data sheet is based on our tests and our practical knowledge. The technical data is defined in standard conditions. Variations in local working conditions and methods will affect the product performance and result. The result is strongly affected by working methods. We guarantee the high quality of our products according to our Quality Management System. No liability can be accepted from incorrect use of the product or prevailing conditions, over which we have no control. Thus, we cannot be held responsible for the final result. The user of the product must test product's suitability to the intended application.

## ENVIRONMENT AND SAFETY

Avoid unnecessary skin contact with and exposure to the fresh product: use safety gloves. Refer to material safety data sheet. For information on product and package disposal, visit [www.kiilto.com](http://www.kiilto.com).

CONSISTENCY	light yellow liquid
DENSITY/SPECIFIC WEIGHT	1.04 - 1.07 kg/dm <sup>3</sup>
VISCOSITY	100 mPas (20 °C)
PACKAGE SIZES	5 l
COVERAGE	Follow machine manufacturer's instructions.
STORAGE	Unopened at +10–25 °C for 6 months