



Kiilto Asetoni



Technical acetone for solvent, thinner or cleaner.

AREA OF APPLICATION

Acetone is intended for grease removal and cleaning of wood, metal, plastic and glass surfaces prior to gluing or surface preparation. Suitable for thinning acetone-based products and for removing different types of adhesive and paint stains.

INSTRUCTIONS FOR USE

When removing grease ensure, via the carrying out of tests if needed, that the material can withstand acetone. Ensure, by studying the instructions of the product to be thinned, that acetone is suitable for thinning. Avoid contact with the skin as acetone dries out skin intensively. Acetone is flammable.

ADDITIONAL INFORMATION

The information given in this product data sheet is based on our tests and our practical knowledge. The technical data is defined in standard conditions. Variations in local working conditions and methods will affect the product performance and result. We guarantee the high quality of our products according to our Quality Management System. No liability can be accepted from incorrect use of the product or prevailing conditions, over which we have no control. Thus, we cannot be held responsible for the final result. The correct use of the product presupposes that the user has made him/herself aware of the contents of the working instructions and procedure guide, if provided.

ENVIRONMENT AND SAFETY

Contains volatile and flammable solvents. Avoid unnecessary skin contact and exposure with the fresh product, use safety gloves. Refer to material safety data sheet. For information on product and package disposal, visit www.kiilto.com.

APPLICATION TEMPERATURE	Lowest +15 °C
FIRE CLASS	Boiling point approx. 56 °C
DENSITY/SPECIFIC WEIGHT	0.8 kg/l
STORAGE	In unopened containers, above +1 °C, for 18 months.