



Sitol 2061



Sitol 2061 is an EVAC-dispersion adhesive for forming and closing of cardboard cases and corrugated cardboard boxes.

COMPLIES WITH
NORDIC
ECOLABEL
REQUIREMENTS



- Ideal properties for nozzles

AREA OF APPLICATION

Sitol 2061 is a non-plasticized ethylene vinyl acetate dispersion adhesive for nozzle application. It is designed for demanding nozzle machinery, e.g. hhs, Nordson-Walcom, Robatech, Dynatech. All components of the adhesive comply with the food packaging regulation FDA 175.105.

INSTRUCTIONS FOR USE

Machinery and instruments can be cleaned with water before the adhesive gets dry. Dried adhesive film can be removed with xylene.

ADDITIONAL INFORMATION

The information given in this product data sheet is based on our tests and our practical knowledge. The technical data is defined in standard conditions. Variations in local working conditions and methods will affect the product performance and result. We guarantee the high quality of our products according to our Quality Management System. No liability can be accepted from incorrect use of the product or prevailing conditions, over which we have no control. Thus, we cannot be held responsible for the final result. The user of the product must test product's suitability to the intended application.

ENVIRONMENT AND SAFETY

Avoid unnecessary skin contact with and exposure to the fresh product: use safety gloves. Refer to material safety data sheet. For information on product and package disposal, visit www.kiilto.com.

TYPE/BINDER	EVAC
DENSITY/SPECIFIC WEIGHT	1,05 kg/dm ³ (20°C)
pH	5
VISCOSITY	650 mPas (Brookfield RVT, 2/20, 20°C)
APPLICATION TEMPERATURE	+18...+25 °C
STORAGE	In unopened containers at +20 °C for 12 months. After prolonged storage, stir before use.