



Kiiltomelt T 4555

Kiiltomelt T 4555 is a multi-purpose, pressure-sensitive, hot-melt adhesive.



- Suitable for e.g. labeling
- Good cold resistance
- Colourless

AREA OF APPLICATION

Kiiltomelt T 4555 is a low viscosity, pressure-sensitive, hot-melt adhesive used for the gluing of labels and for reducing the slipperiness of corrugated board boxes, paper and plastic bags in palletising. All components of the adhesive comply with the food packaging regulation FDA 175.105.

INSTRUCTIONS FOR USE

Packed in a plastic foil. Plastic foil melts with the adhesive. Suitable application methods are by nozzle, disc and roller.

ADDITIONAL INFORMATION

The information given in this product data sheet is based on our tests and our practical knowledge. The technical data is defined in standard conditions. Variations in local working conditions will affect the product performance and result. The result is also strongly affected by working methods. We guarantee the high quality of our products according to our Quality Management System. No liability can be accepted from incorrect use of the product or prevailing conditions, over which we have no control. Thus, we cannot be held responsible for the final result. The user of the product must test product's suitability to the intended application.

ENVIRONMENT AND SAFETY

Avoid unnecessary skin contact with and exposure to the fresh product: use safety gloves. Refer to material safety data sheet. For information on product and package disposal, visit www.kiilto.com.

COLORS	Almost colourless
SOFTENING POINT	80 °C
VISCOSITY	1100 mPas, (140 °C)
OPEN TIME	Long (pressure sensitive adhesive)
APPLICATION TEMPERATURE	130–140 °C
PACKAGE SIZES	18 kg
STORAGE	In unopened containers, at max. +40 °C, for 24 months.