

Sitol 4678



KIILTO INDUSTRIAL ADHESIVES

Sitol 4678 is a PVAC dispersion adhesive for spiral-wound core manufacture.

COMPLIES WITH
NORDIC
ECOLABEL
REQUIREMENTS



- Good roller properties

AREA OF APPLICATION

Sitol 4678 is a modified polyvinyl acetate dispersion adhesive. The adhesive has good roller application properties. Sitol 4678 is suitable for laminating carton, cardboard and paper. Ideal for gluing the top carton of spiral-wound tubes.

INSTRUCTIONS FOR USE

Machinery and instruments can be cleaned with water before the adhesive gets dry. Dried adhesive film can be removed with xylene.

ADDITIONAL INFORMATION

The information given in this product data sheet is based on our tests and our practical knowledge. The technical data is defined in standard conditions. Variations in local working conditions and methods will affect the product performance and result. We guarantee the high quality of our products according to our Quality Management System. No liability can be accepted from incorrect use of the product or prevailing conditions, over which we have no control. Thus, we cannot be held responsible for the final result. The user of the product must test product's suitability to the intended application.

ENVIRONMENT AND SAFETY

Avoid unnecessary skin contact with and exposure to the fresh product: use safety gloves. Refer to material safety data sheet. For information on product and package disposal, visit www.kiilto.com.

TYPE/BINDER	PVAc
DENSITY/SPECIFIC WEIGHT	1,15 kg/dm
pH	7
VISCOSITY	4300 mPas, Brookfield RVT 4/20, 20°C
APPLICATION TEMPERATURE	+18...+25 °C
STORAGE	In unopened containers at +20 °C for 12 months. After prolonged storage, stir before use.