

Sitol 6740



Sitol 6740 is a polyvinyl alcohol adhesive for gluing building insulation materials.



AREA OF APPLICATION

Sitol 6740 is designed for bonding of fibre-based house-insulating materials with nozzle/spray applicator. Dries slowly and creates a strong bond. Compatible with Ekovilla's cellulose insulation, (VTT, ETA 09/0081) and Termex's cellulose insulation (VTT-C-11413-15).

INSTRUCTIONS FOR USE

Machinery and instruments can be cleaned with water before the adhesive gets dry. Dried adhesive can be removed mechanically and finished with warm water.

ADDITIONAL INFORMATION

The information given in this product data sheet is based on our tests and our practical knowledge. The technical data is defined in standard conditions. Variations in local working conditions and methods will affect the product performance and result. We guarantee the high quality of our products according to our Quality Management System. No liability can be accepted from incorrect use of the product or prevailing conditions, over which we have no control. Thus, we cannot be held responsible for the final result. The user of the product must test product's suitability to the intended application.

ENVIRONMENT AND SAFETY

Avoid unnecessary skin contact with and exposure to the fresh product: use safety gloves. Refer to material safety data sheet. For information on product and package disposal, visit www.kiilto.com.

TYPE/BINDER	Polyvinyl alcohol adhesive
DENSITY/SPECIFIC WEIGHT	1,05 kg/dm ³ (20°C)
pH	7
VISCOSITY	3,500 mPas (Brookfield RVT, 3/20, 20°C)
APPLICATION TEMPERATURE	+18...+25 °C
STORAGE	In unopened containers at +20 °C for 12 months. After prolonged storage, stir before use.