



Kiiltomelt V 159



Kiiltomelt V 159 is an all-purpose EVAC-hot melt adhesive for the paper and packaging industry.



- Low working temperature

AREA OF APPLICATION

Kiiltomelt V 159 is used for sealing and assembling of corrugated and cardboard packages and as a packing adhesive in ream wrapping and roll packing departments. It can be used at much lower temperatures than traditional hot melt adhesives. Reduces machine maintenance hours. All components of the adhesive comply with the food packaging regulation FDA 175.105.

INSTRUCTIONS FOR USE

Suitable application methods are nozzle and roller.

ADDITIONAL INFORMATION

The information given in this product data sheet is based on our tests and our practical knowledge. The technical data is defined in standard conditions. Variations in local working conditions will affect the product performance and result. The result is also strongly affected by working methods. We guarantee the high quality of our products according to our Quality Management System. No liability can be accepted from incorrect use of the product or prevailing conditions, over which we have no control. Thus, we cannot be held responsible for the final result. The user of the product must test product's suitability to the intended application.

ENVIRONMENT AND SAFETY

Avoid unnecessary skin contact and exposure with the fresh product, use safety gloves. Refer to material safety data sheet. For information on product and package disposal, visit www.kiilto.com.

COLORS	yellowish and blue
SOFTENING POINT	104 °C (DIN 52011)
VISCOSITY	1200 mPas, 140 °C, 100 s ⁻¹
OPEN TIME	Short (130 °C)
APPLICATION TEMPERATURE	120–150 °C
PACKAGE SIZES	10 kg
STORAGE	In unopened containers, at max. +40 °C, for 36 months