

Sitol 7060E



Sitol 7060E is a glass-bottle labelling adhesive



- Good wet tack
- Highly viscous
- Suitable for food packages

AREA OF APPLICATION

Sitol 7060E is suitable for gluing labels onto glass and metal. The adhesive has good wet tack and good resistance against condensing water.

Maximum line speed 60,000 bottles/hour (note that different parameters may cause case-specific variation in speed).

INSTRUCTIONS FOR USE

Machinery and instruments can be cleaned with water before the adhesive gets dry. Dried adhesive can be removed mechanically and finished with hot water.

ADDITIONAL INFORMATION

The information given in this product data sheet is based on our tests and our practical knowledge. The technical data is defined in standard conditions. Variations in local working conditions and methods will affect the product performance and result. The result is strongly affected by working methods. We guarantee the high quality of our products according to our Quality Management System. No liability can be accepted from incorrect use of the product or prevailing conditions, over which we have no control. Thus, we cannot be held responsible for the final result. The user of the product must test product's suitability to the intended application.

ENVIRONMENT AND SAFETY

Avoid unnecessary skin contact with and exposure to the fresh product: use safety gloves. Refer to material safety data sheet. For information on product and package disposal, visit www.kiilto.com.

TYPE/BINDER	Modified starch adhesive
DENSITY/SPECIFIC WEIGHT	1,15 kg/dm
pH	7.5
VISCOSITY	73 000 mPas Brookfield RVT, 7/20, 20 °C
WORKING CONDITIONS	18 ... 30 °C
STORAGE	Unopened package at +1°C / 9 months, +20° C / 6 months, +40°C / 2 months. After prolonged storage, stir before use.